PLAT OF SURVEY

PARCEL A

That part of the Southeast and Southwest 1/4s of the Southeast ¼ of Section 14 and the Northeast, Northwest, Southeast and Southwest 1/4s of the Northeast ¼ of Section 23 and the Northwest ¼ of the Northwest ¼ of Section 24, Town 2 North, Range 7 East, Town of Monroe, Green County, Wisconsin, bounded and described as follows:

Beginning at a concrete monument with brass cap at the Northeast corner of Section 23; thence S00°00'24"E, 665.53' to an iron rod at the Northwest corner of the South ½ of the Northwest ¼ of the Northwest ¼ of Section 24; thence \$89.50.33"E along the North line of the South ½ of the Northwest ¼ of the Northwest ¼ of Section 24, 158.54' to an iron rod on the Westerly right-of-way line of the former Illinois Central Railroad; thence S17°44'14"W along said right-of-way line, 492.25' to an iron rod: thence Southwesterly, 1008.74' along said right-of-way line and the arc of a curve to the left whose radius is 5779.65' and whose chord bears \$12.44'14"W, 1007.46' to an iron rod; thence \$07.44'14"W along said right-of-way line. 548.16' to an iron pipe on the East-West ¼ line of Section 23; thence N89°42'16"W along the East-West ¼ line of Section 23, 2351.23' to an iron rod on the Easterly right-of-way line of State Trunk Highway 69; thence NO2'32'20"E along said right-of-way line, 33.03' to an iron rod; thence S89°42'16"E along said right—of—way line, 17.01' to an iron rod; thence N02°32'20"E along said right—of—way line, 33.03' to an iron rod; thence S89°42'16"E, 1294.03' to an iron rod on the West line of the Southeast ¼ of the Northeast ¼ of Section 23: thence N00°00'16"E. 1928.08' to an iron rod at the Southwest corner of the North 1/2 of the Northeast 1/4 of the Northeast ¼ of Section 23; thence N71°44'41"W, 601.92' to an iron rod; thence N00°23'09"W. 474.96' to an iron rod; thence N71° 25'31"W, 436.69' to an iron rod; thence S84*21'32"W, 253.96' to an iron rod on the Easterly right—of—way line of State Trunk Highway 69; thence N00°06'40"W along said right-of-way line, 610.13' to an iron rod; thence S89°53'20"W along said right—of—way line, 35.00' to an iron rod; thence N00°06'40"W along said right—of—way line, 500.33' to an iron rod; thence N08° 38'31"W along said right-of-way line, 101.12' to an iron rod on the North line of the Southwest ¼ of the Southeast ¼ of Section 14; thence S89°49'44"E, 2607.55' to an iron rod at the Northeast corner of the Southeast ¼ of the Southeast ¼ of Section 14; thence S00'27'48"E, 1319.04' to the point of beginning.

PARCEL B

That part of the Southeast ¼ of the Northeast ¼ of Section 23 and the Southwest and Northwest 1/4s of the Northwest ¼ of Section 24, Town 2 North, Range 7 East, Town of Monroe, Green County, Wisconsin, bounded and described as follows: Beginning at a concrete monument with brass cap at the East ¼ corner of Section 23; thence N89°42'16"W along the East-West 1/4 line of Section 23, 186.73' to an iron rod on the Easterly right-of-way line of the former Illinois Central Railroad: thence NO7° 44'14"E along said right—of—way line, 535.10' to an iron rod; thence Northeasterly, 991.29' along said right—of—way line and the arc of a curve to the right whose radius is 5679.65' and whose chord bears N12°44'14"E, 990.03' to an iron rod; thence N17° 44'14"E along said right-of-way line, 523.93' to an iron rod on the North line of the South ½ of the Northwest ¼ of the Northwest ¼ of Section 24: thence S89°50'33"E. 1040.00' to an iron rod at the Northeast corner of the South ½ of the Northwest ¼ of the Northwest ¼ of Section 24; thence S00°03'15"W, 1993.75' to an iron rod at the Southeast corner of the Southwest ¼ of the Northwest ¼ of Section 24; thence N89°58'04"W, 1301.32' to the point of beginning.

I hereby certify that I have surveyed, monumented, and mapped the lands described hereon. representation thereof in accordance with the information provided.

May 12, 2004

C.S.M. 1228

---- NO8*38'31"W

—— S89°53'20"W

35.00'

VARIABLE

101.12'

1.) Bearings are referenced to the East-West 1/4 line of Section 23, which was assumed to bear N89°42'16"W.

2.) Recorded data, when different than measured, is shown in parenthesis. 3.) The driveway from S.T.H. 69 that serves Parcels A and B also serves Lot 1 of Certified Survey Map 1671.

Concrete monument with brass cap found.

Cast aluminum monument found.

1" o.d. iron pipe found.

3/4" solid round iron rebar found.

3/4" X 24" solid round iron rebar set.

CURVE	DATA
CONVL	DAIR

Curve	Radius	Length	Delta	Chord	Chord Bear.
1-2	5779.65'	1008.74	10.00,00"	1007.46	S 12'44'14" W
3-4	5679.65	991.29'	10.00,00"	990.03'	N 12'44'14" E

GRAPHIC SCALE - FEET SCALE: 1" = 200'

PREPARED FOR: Century 21 Zwygart Real Estate c/o Bub Zwygart 910 17th Avenue Monroe, WI 53566 (608) 329-2200

> TALARCZYK & ASSOC., INC. W5105 KUBLY ROAD P.O. BOX 235 NEW GLARUS, WI 53574 PHONE 608/527-5216

FAX 608/527-5357



VARIABLE

SHORT LINE TABLE Distance ∕—17.6' SOUTH OF FENCE S89'42'16"E 1294.03' 9.6' SOUTH & 26.7' EAST OF FENCE CORNER 2351.23 N89°42'16"W --- 17.2' SOUTH OF FENCE (N89°42'01"W) (N89°44'41"W) <u>LOT 1 C.S.M.</u> 1671

(S89°49'48"E) S89'49'44"E

2607.55

PARCEL A

162.25 ACRES

S89'50'33"E — EXISTING DRIVE CROSSING TRAIL 186.73' (23 24) (S89°47'55"W)

PARCEL B 59.83 ACRES

> 1.0' NORTH & 5.1' WEST OF FENCE CORNER 1301.32' N89'58'04"W

-39.1' SOUTH & 6.9' WEST OF FENCE CORNER

JOB NO. 04045 POINTS 04045 DRWG. 04045 CHECKED FAT

DRAWN BY RAT