

# PLAT OF SURVEY

That part of the SE 1/4 of the NW 1/4 of Section 36, Town 2 North, Range 9 East, City of Brodhead, Green County, Wisconsin, bounded and described as follows:

Commencing at the Center of Section 36; thence S89°42'53"W, 198.40' to the point of beginning; thence S89°42'53"W along said S. line, 459.99'; thence N0°15'26"W, 594.09' to the southerly right-of-way of 25th Street; thence N89°47'15"E along said southerly right-of-way, 302.55'; thence Northeasterly, 22.80' along the arc of a curve to the left, whose radius is 335.00' and whose chord bears N87°50'16"E, 22.80'; thence S0°15'19"E, 130.78'; thence N89°47'15"E, 280.23' to the westerly right-of-way of S.T.H. 11; thence S0°15'16"E along said westerly right-of-way, 253.14'; thence S34°26'11"W along said westerly right-of-way, 255.72' to the point of beginning; subject to any and all easements of record.

I, Todd E. Hasse, Registered Land Surveyor, S-2228, hereby certify that I have made this Plat of Survey under the direction of Randall & Teresa Gobeli and that I have surveyed, monumented and mapped the lands described hereon and that this map is a correct representation thereof in accordance with the information provided.

September 6th, 2005

*Todd E. Hasse*  
Todd E. Hasse R.L.S. - 2228



### LEGEND:

- 3/4" solid round iron rod found.
- Concrete monument with brass cap found.
- 3/4" solid round iron rod found.
- 1 1/4" solid round iron rod found.
- 3/4" X 24" solid round iron rod set, weighing 1.50 lbs per lineal ft.
- Existing fence line.

### CURVE DATA:

CURVE	RADIUS	INT. ANGLE	ARC	CHORD	CHORD BEARING	TANGENT BEARING
1-2	335.00'	3°53'58"	22.80'	22.80'	N87°50'16"E	⊙ N85°53'17"E


### NOTE:

Bearings are referenced to the S. line of the NE 1/4 of Section 36, which was assumed to bear S89°42'53"W.



SCALE: 1" = 60'

GRAPHIC BAR SCALE:



### PREPARED FOR:

Randall & Teresa Gobeli  
623 30th Street  
Monroe, WI 53566  
(608) 328-8395

JOB NO. 05071  
DRAWING C: \DRAWINGS\PLATS\05071.DWG

